# HYDROFLOW Easy Vent



Compact roof ventilator for efficient air circulation and condensation removal in bathrooms, toilets, laundries, and kitchens.



Scan to find our Easy Vent Installation Guide

### **Features and Benefits**

- Three completemodels. TileRoof, Corrugated Roofing and Rural Corregated Roof all include EPDM and Silicone Roof Seal.
- Low Profile
- All Metal Construction
- Black is standard, with 8 new colour options at an additional cost
- Special Rural product for Fire Zone 29 Areas, plus insect protective mesh
- Can be Installed anywhere on Metal and Tile Roof
- Quick and Easy to Install
  - Complies with NCC PART 3.8.7.3 Flow Rate and Discharge of Exaust Systems

#### **VENT COWL NEW COLOUR OPTIONS**



Shale Grey

Aluminium



Beige

Surf Mist

Dune









METAL ROOF RURAL CORRUGATED ROOF

## **HYDROFLÔW**

### **Easy Vent**

### Installation Guide



Select a suitable location for the Hydroflow Easy Vent on either a tiled roof surface or a metal roof surface. Mark tile and cut to allow for the flue to pass through the roof to the atmosphere. For metal roofs, mark a circular diameter of 155mm and cut a hole.



Fit the Easy Vent flue through the prepared space. The outer ring of the flue will come to rest on the rooftop surrounding the prepared space.

The Easy Vent can be secured directly to the metal roof using screws or rivets.

Tile roof securing is aided by the use of the additional securing ring supplied in the tile roof kit.



Fit metal or tile roof seal over the flue and seal/secure to roof.



Fit the Easy Vent cowl to the top of the flue, and secure it with supplied pop rivets.

\*NOTE\* - INSTALLATION SHOULD ONLY BE CARRIED OUT BY SUITABLY QUALIFIED AND LICENCED PRACTITIONERS IN ACCORDANCE WITH AUSTRALIAN STANDARD AS3500



#### Optional:

Ember Attack Fire mesh Protection and insect protection available as per AS3959- 2018 Amdt1 Where Required for Bushfire Risk Management For more information on this product visit hydroflow.com.au or scan the QR code









