

# HYDROFLOW

LEADING WITH KNOWLEDGE

## NON RETURN VALVES - SWING CHECK VALVE GENERAL PURPOSE

Code	Description
SW15	SWING CHECK VALVE WM 15MM BSP
SW20	SWING CHECK VALVE WM 20MM BSP
SW25	SWING CHECK VALVE WM 25MM BSP
SW32	SWING CHECK VALVE WM 32MM BSP
SW40	SWING CHECK VALVE WM 40MM BSP
SW50	SWING CHECK VALVE WM 50MM BSP
SW65	SWING CHECK VALVE WM 65MM BSP
SW80	SWING CHECK VALVE WM 80MM BSP
SW100	SWING CHECK VALVE WM 100MM BSP



### Features and Specifications

- DR Brass
- Can be installed vertical or horizontal
- Excellent flow rates
- Temperature range 0C to 80 0C
- Max. working pressure 1600KPa

### Component Material -

- O-Ring - Rubber
- Check disk - Brass
- Body - Brass
- Cap - Brass
- Pin - Stainless Steel

Hydroflow Distributors (Aust) Pty Ltd

24 Harcourt Road, Altona, VIC, 3018. T +613 8369 9500 Ph 1300 493 359 F: +613 9676 9268