

Code	Description	Size
FLEXIBLE HOSES - S/S BRAIDED AND UNBRAIDED, CUSTOM LENGTHS AND END CONNECTIONS		

FLEXIBLE HOSE

S/S Flexible Braided Hose Available in Sizes 15mm-200mm, various Lengths and End Connections (Threaded, Flanged, Grooved). Please contact Sales for all Enquiries.

SCREWED VALVES AND STRAINERS

BUGATTI BALL VALVES - SCREWED

- Dual Approved Watermark and AGA Approved High Quality Italian Made Bugatti DR Brass Ball Valves.
- Lever Handle - Threaded Female/Female and Male/Female. Lockable Options.
- Maximum Working Pressure: 2100Kpa Temperature Range Water: 0.5 - 120C (Intermittent)

FEMALE X FEMALE BSP LOCKABLE

- BG636GWL.15
- BG636GWL.20
- BG636GWL.25
- BG636GWL.32
- BG636GWL.40
- BG636GWL.50

- 15mm
- 20mm
- 25mm
- 32mm
- 40mm
- 50mm



MALE X FEMALE BSP LOCKABLE

- BG656GWL.15
- BG656GWL.20
- BG656GWL.25
- BG656GWL.32
- BG656GWL.40
- BG656GWL.50


- 15mm
- 20mm
- 25mm
- 32mm
- 40mm
- 50mm



FEMALE X FEMALE BSP

- BG636GW.15
- BG636GW.20
- BG636GW.25
- BG636GW.32
- BG636GW.40
- BG636GW.50

- 15mm
- 20mm
- 25mm
- 32mm
- 40mm
- 50mm



Code	Description	Size
MINI BALL VALVES (GAUGE COCKS)		
GENERAL PURPOSE MINI BALL VALVES C/P - SCREWED		
Female/Female		
MBVFF06		6mm Fem x Fem
MBVMF06		6mm Male x Fem
MBVFF10		10mm Fem x Fem
MBFMF10		10mm Male x Fem



SECTION 11

SPRING CHECK VALVES - SCREWED, C/P, WATERMARK APPROVED

WSP15		15mm
-------	--	------

SPRING CHECK VALVES - SCREWED

GENERAL PURPOSE SPRING CHECK VALVE BR WITH NYLON PISTON

SP15		15mm
SP20		20mm
SP25		25mm
SP32		32mm
SP40		40mm
SP50		50mm



SWING CHECK VALVES - SCREWED

GENERAL PURPOSE SWING CHECK VALVE BR - SCREWED

SW15		15mm
SW20		20mm
SW25		25mm
SW32		32mm
SW40		40mm
SW50		50mm



Code **Description** **Size**

GATE VALVES - SCREWED

GENERAL PURPOSE GATE VALVES BR - SCREWED

GV01	15mm
GV02	20mm
GV03	25mm
GV04	32mm
GV05	40mm
GV06	50mm



Y STRAINERS - SCREWED

GENERAL PURPOSE Y STRAINERS BR - SCREWED

BYS15	15mm
BYS20	20mm
BYS25	25mm
BYS32	32mm
BYS40	40mm
BYS50	50mm



HVAC WM BALL VALVES W TEST POINTS

WATERMARK APPROVED HVAC BALL VALVES WITH TEST PLUGS

HVW10F	10mm
HVW15F	15mm
HVW20F	20mm
HVW25F	25mm
HVW32F	32mm
HVW40F	40mm
HVW50F	50mm

TEST PLUG (HVAC SCREWED WITH CAP)

Code	Description	Size
TP06		6mm

WATTS AUTOMATIC AIR VENTS

- Watts Series FV-4MI Automatic Air Vents are made of brass with silicon rubber seals and polyethylene float.
- Suitable for use with water and glycol systems
- Pressure Range: 10Kpa - 1000Kpa Temperature Range: 5°C - 116°C

FV-4MI		1/8" (3mm)
FV-4MI-6		1/4" (6mm)
FV-4MI-15		1/2" (15mm)
FV-4MI-20		3/4" (20mm)
FV-4MI-25		1" (25mm)



SECTION 11

SOLENOID VALVES

- GEM - Brass Body, S/S Operator, NBR Seals, Coil voltage ± 10%, DC 10W, IP65, Temp: Fluid -10°C to 80°C / Ambient: -10°C to 50°C, Pressure: 0.5 to 20bar, KV - 35 L/m
- Burkert 5282 - Brass Body, NBR Seals, Coil voltage ± 10%, DC ,IP65, Temp: Ambient +55°C, Pressure: 0.2 to 10bar.
- *Circuit function of the Burkert valve can be changed by turning the pilot drive 180°

GEM SOLENOID VALVES UL

GEM-S-2401N2	GEM SERVO BRASS 2W N/C 1/2" BSP NBR w Manual Override
GEM-S-2401N4	GEM SERVO BRASS 2W N/C 1/2" BSP NBR w Push Lock M/O
GEM-S-2402N4	GEM SERVO BRASS 2WNO 1/2" BSP NBR w Push Lock M/O & Copper Tube
GEM-B-331	GEM COIL and CONNECTION 24V DC 10W (required with each valve)



BURKERT 5282 SOLENOID VALVES UL

SOL-282-2415-MA	Burkert 5282 Pilot Operated Solenoid Valve 24v 15mm N/O and N/C, M/O
-----------------	--

SOLENOID TEST ASSEMBLIES

Code	Description	Size
SOLTESTASSY	Solenoid Valve Test Arrangement	

SECTION 11

GAUGES

PRESSURE GAUGES

63MM DIA FACE - S/S CASE, BRASS/BRONZE WETTED PARTS, BOTTOM ENTRY 1/4" BSPT, GLYCERINE FILLED (L63). DUAL SCALE KPA/PSI.

RB1613850	L63 X -100kPa VACUUM
RB1613900	L63 X 100kPa / 15PSI
RB1613950	L63 X 250kPa / 55PSI
RB1614000	L63 X 400kPa / 55PSI
RB1614050	L63 X 600kPa / 85PSI
RB1614100	L63 X 800kPa / 115PSI
RB1614150	L63 X 1000kPa/ 145PSI
RB1614200	L63 X 1600kPa/ 230PSI
RB1614250	L63 X 2500kPa/350PSI
RB1614300	L63 X 4000kPa/ 600PSI
RB1614325	L63 X 6000kPa/ 870PSI
RB1614350	L63 X 8000kPa/1160PSI
RB1614400	L63 X10000kPa/1500PSI
RB1614450	L63 X16000kPa/2320PSI
RB1614520	L63 X25000kPa/3600PSI
RB1614580	L63 X40000kPa/5800PSI

** Centre Back Entry Gauges available on request.*

100 MM DIA FACE, S/S CASE, BRASS/BRONZE WETTED PARTS, LOWER MOUNT (LM), 3/8" BSPT, GLYCERINE FILLED (L100). DUAL SCALE KPA/PSI.

RB1618525	L100 X -100/0/150kPa
RB1618530	LX100 X 250kPa/ 36PSI
RB1618540	LX100 X 400kPa/ 60PSI
RB1618560	LX100 X 800kPa/ 115PSI
RB1618570	LX100 X 1000kPa/ 145PSI
RB1618580A	LX100 X 1600kPa/230PSI
RB1618590	LX100 X 2500kPa/ 360PSI
RB1618600	LX100 X 4000kPa/ 580PSI
RB1618625	L100 X 25000kPa/3600PSI

Code **Description** **Size**

**Centre Back Entry Gauges available on request.*

TEMPERATURE GAUGES

REAR ENTRY BI-METAL THERMOMETER, ALL STAINLESS, 80MM DIA, BACK ENTRY (CBM), ZERO ADJUST, 100MM STEM LENGTH, 1/2" NPT.

TEMPGAUGE-50-50	-50/50
TEMPGAUGE0-50	0/50
TEMPGAUGE0-70	0/70
TEMPGAUGE0-100	0/100
TEMPGAUGE0-120	0/120
TEMPGAUGE0-150	0/150
TEMPGAUGE0-200	0/200
RB2629904	Accessories - Thermowell

** 63mm and 125mm DIA Faces and Various Stem Lengths available on request*

ADJUSTABLE ANGLE HEAD BI-METAL THERMOMETER, ALL STAINLESS, 80MM DIA ADJUSTABLE ANGLE HEAD, WITH 100MM STEM LENGTH

RB2623922	-50/+50
RB2623932	0/70
RB2623942	0/120
RB2623952	0/200
RB2623992	0/400
RB2629904	Accessories - Thermowell

Additional Gauges - Available on Request

50MM DIA PRESSURE GAUGES, BRASS/BRONZE WETTED PARTS, LOWER MOUNT (LM) OR CENTRE BACK ENTRY (CBM), 1/4" BSPT, DUAL SCALE KPA/PSI.

- Black Steel Case rather than S/S Case Option
- Dry rather than Liquid Filled Option
- Additional Pressure Gauge Types - Digital; Industrial; Low Pressure
- Special Purpose Gauges - Valve Positioner Gauges and Pool Filter Gauge
- Portable Testing Gauge
- "Gauge Accessories - Panel Mount via front flange or panel mount kit is only available for stainless steel cased gauges; Back flange only suitable black steel case; Glass lens only suitable for black steel case"
- Additional Thermometer Types - Remote Reading; V-Form; Digital Thermometers

Code **Description** **Size**

ERICO PIPE HANGERS, CHANNEL AND ROD

BEAM CLAMP

- Cast Iron
- ElectroGalvanised

ER389500	TK300-9mm
ER389510	TK300-11mm
ER389521	TK300-13mm



CADDY 429 MACROFIX PLUS (CPVC)

- Steel
- ElectroGalvanised

ER595052	15nb (20 - 21.3mm) M10
ER595053	20nb (25 - 26.9mm) M10
ER595054	25nb (32 - 33.7mm) M10
ER595056	32nb (40 - 42.4mm) M10
ER595057	40nb (48.3 to 50mm) M10
ER595059	50nb (60.3 - 63mm) M10
ER595061	65nb (75 - 76.1mm) M10
ER596060	80nb (88.9 - 90mm) M10
ER595062	100nb (110 - 114.3mm) M10
ER596062	65nb (75 - 76.1mm) M12
ER595063	80nb (88.9 - 90mm) M12
ER596063	100nb (110 - 114.3mm) M12



ADJUSTABLE CLAMP

- Steel
- Hot Dip Galvanised

ERADJ-020-GWIR-HDG	20nb
ERADJ-025-GWIR-HDG	25nb
ERADJ-032-GWIR-HDG	32nb
ERADJ-040-GWIR-HDG	40nb
ERADJ-050-GWIR-HDG	50nb
ERADJ-065-GWIR-HDG	65nb
ERADJ-080-GWIR-HDG	80nb
ERADJ-100-GWIR-HDG	100nb
ERADJ-125-GWIR-HDG	125nb
ERADJ-150-GWIR-HDG	150nb



Code **Description**

Size

DEEP SADDLE

- Steel
- ElectroGalvanised

ERCDS32
ERCDS40
ERCDS50

32nb EG
40nb EG
50nb EG



SHALLOW SADDLE

- Steel
- ElectroGalvanised

ERCLS25
ERCLS32
ERCLS40
ERCLS50
ERCLS65

25nb
32nb
40nb
50nb
65nb



TWIST CLIP

- Steel
- PreGalvanised

ERCTC25
ERCTC32
ERCTC40
ERCTC50
ERCTC65

25nb
32nb
40nb
50nb
65nb



CHANNEL CLIP

- Steel
- Galvanised

ERCHC-015-GWIR-GAL
ERCHC-020-GWIR-GAL
ERCHC-025-GWIR-GAL
ERCHC-032-GWIR-GAL
ERCHC-040-GWIR-GAL
ERCHC-050-GWIR-GAL
ERCHC-065-GWIR-GAL
ERCHC-080-GWIR-GAL
ERCHC-100-GWIR-GAL
ERCHC-125-GWIR-GAL
ERCHC-150-GWIR-GAL
ERCHC-200-GWIR-GAL
ERCHC-250-GWIR-GAL

15nb
20nb
25nb
32nb
40nb
50nb
65nb
80nb
100nb
125nb
150nb
200nb
250nb



Code	Description	Size
CHANNEL CLIP		
	<ul style="list-style-type: none"> Steel Hot Dip Galvanised 	
ERCHC-015-GWIR-HDG		15nb
ERCHC-020-GWIR-HDG		20nb
ERCHC-025-GWIR-HDG		25nb
ERCHC-032-GWIR-HDG		32nb
ERCHC-040-GWIR-HDG		40nb
ERCHC-050-GWIR-HDG		50nb
ERCHC-065-GWIR-HDG		65nb
ERCHC-080-GWIR-HDG		80nb
ERCHC-100-GWIR-HDG		100nb
ERCHC-125-GWIR-HDG		125nb
ERCHC-150-GWIR-HDG		150nb
ERCHC-200-GWIR-HDG		200nb
ERCHC-250-GWIR-HDG		250nb

CADDY HORIZONTAL MOUNTING PLATE

	<ul style="list-style-type: none"> ElectroGalvanised 	
ERCMP10		M10
ERCMP8		M8
ERCMP12		M12

CADDY VERTICAL MOUNTING PLATE

	<ul style="list-style-type: none"> Steel ElectroGalvanised 	
ERVMP10		M10
ERVMP8		M8
ERVMP12		M12



Code	Description	Size
NUT CLIP		
<ul style="list-style-type: none"> • Steel • ElectroGalvanised 		
ERCNC20		20nb
ERCNC25		25nb
ERCNC32		32nb
ERCNC40		40nb
ERCNC50		50nb
ERCNC65		65nb
ERCNC65M12		65nb M12
ERCNC80		80nb
ERCNC80M12		80nb M12
ERCNC100		100nb
ERCNC100M12		100nb M12
ERCNC125		125nb
ERCNC125M12		125nb M12
ERCNC150		150nb
ERCNC150M12		150nb M12



PEAR BANDS

- Steel
- ElectroGalvanised

EREPB27		20nb
EREPB34		25nb
EREPB43		32nb
EREPB48		40nb
EREPB60		50nb
EREPB76		65nb
EREPB89		80nb
EREPB114		100nb
EREPB165		150nb
EREPB220		200nb



MEDIUM DUTY SADDLE CLAMPS

ERERIC15-60		50nb
ERERIC15-76		65nb
ERERIC15-89		80nb
ERERIC15-114		100nb
ERERIC15-165		150nb
ERERIC15-219		200nb



Code **Description** **Size**


MEDIUM DUTY 2 PIECE CLAMP - HDG

ERERIC16-60	Steel 50nb
ERERIC16-76	Steel 65nb
ERERIC16-89	Steel 80nb
ERERIC16-102	Copper 100mm
ERERIC16-114	Steel 100nb
ERERIC16-127	Copper 125mm
ERERIC16-140	Steel 125nb
ERERIC16-152	Copper 150mm
ERERIC16-165	Steel 150nb
ERERIC16-220	Steel 200nb
ERERIC16-273	Steel 250nb



ADJUSTABLE CLAMP HDG

ERERIC18-60	Steel 50nb
ERERIC18-76	Steel 65nb
ERERIC18-89	Steel 80nb
ERERIC18-114	Steel 100nb
ERERIC18-127	Copper 125mm
ERERIC18-152	Copper 150mm
ERERIC18-165	Steel 150nb
ERERIC18-219	Steel 200nb
ERERIC18-273	Steel 250nb



BRACED CANTILEVER ARMS

ERECB150	320mm
ERECB300	470mm
ERECB450	635mm
ERECB600	780mm




CANTILEVER ARM - HDG

ERKH6C	250mm
ERKH11C	300mm
ERKH12C	450mm
ERKH13C	600mm
ERKH14C	750mm



Code	Description	Size
CADDY CHANNEL "ERISTRUT"		
ERES1000		41 x 41 x 2.5mm (3m)
ERES1000T		41 x 41 x 2.5mm (3m)
ERES3300		41 x 41 x 2.5mm (3m)
ERES3300T		41 x 41 x 2.5mm (3m)
ERES4121PLX6		41 x 41 x 2.5mm (6m)
ERES4121SLOTX6		41 x 41 x 2.5mm (6m)
ERES4141PLX6		41 x 41 x 2.5mm (6m)
ERES4141SLOTX6		41 x 41 x 2.5mm (6m)



SLOTTED ANGLE - EG		
EREA3030		30 x 30mm
EREA5050		50 x 50mm



CHANNEL NUT WITH SPRING		
ER315085		UA 506 M6
ER315095		UA 608 M8
ER315105		UA 810 M10
ER315115		UA 812 M12



TWO PIECE CLIP		
ERTPC-015-GWIR-HDG		15nb
ERTPC-020-GWIR-HDG		20nb
ERTPC-025-GWIR-HDG		25nb
ERTPC-032-GWIR-HDG		32nb
ERTPC-040-GWIR-HDG		40nb
ERTPC-050-GWIR-HDG		50nb
ERTPC-065-GWIR-HDG		65nb
ERTPC-080-GWIR-HDG		80nb
ERTPC-100-GWIR-HDG		100nb
ERTPC-125-GWIR-HDG		125nb
ERTPC-150-GWIR-HDG		150nb

THREADED ROD - ZP		
ERROD-M10X3-ZP		M10 x 3m
ERROD-M12X3-ZP		M12 x 3m

Code	Description	Size
DROP IN ANCHOR - ZP		
ER593200		M10 x 30
ER593205		M12 x 50



PURLIN CLIPS		
ERE210		E2 - M10
ERE212		E2 - M12



Other items available on request please contact sales for all enquiries

HYDRANTS, BOOSTERS, HOSES AND ACCESSORIES

HYDRANT VALVES, ASSEMBLIES AND ACCESSORIES

STAINLESS STEEL LANDING VALVES (MILLCOCKS) WM - OBLIQUE OUTLET (CFA,MFB,STORTZ,QRT,NSW,SA)

ROLL GROOVE INLET 80MM

HVCFARG-SSC	80mm RG x CFA c/w Cap
HV5VRG-SSC	80mm RG x 5vt MFB c/w Cap
HVSTZRG-SSC	80mm RG x STORTZ c/w Cap
HVQRTRG-SSC	80mm RG x QRT c/w Cap
HVNSWRG-SSC	80mm RG x NSW c/w Cap
HVSARG-SSC	80mm RG x SA c/w Cap



THREADED INLET 65MM BSP

HVCFABS-SSC	65mm BSP (M) x CFA c/w Cap
HV5VBS-SSC	65mm BSP (M) x 5vt MFB c/w Cap
HVSTZBS-SSC	65mm BSP (M) x STORTZ c/w Cap
HVQRTBS-SSC	65mm BSP (M) x QRT c/w Cap
HVNSWBS-SSC	65mm BSP (M) x NSW c/w Cap
HVSABS-SSC	65mm BSP (M) x SA c/w Cap



Code **Description** **Size**

**STAINLESS STEEL LANDING VALVES WM - RIGHT ANGLED OUTLET (NSW,QRT,SA,BSP,BI)
ROLL GROOVE INLET 80MM**

PHV -NSW-SS	R/A 80/G Inlet X NSW Outlet
PHV -SA-SS	R/A 80/G Inlet X SA Outlet
PHV -QRT-SS	R/A 80/G Inlet X QRT Outlet
PHV -BSP-SS	R/A 80/G Inlet X BSP Outlet
PHV -BI-SS	R/A 80/G Inlet X BI Outlet



SECTION 11

THREADED INLET 65MM BSP

PHV -65BSP-NSW-SS	R/A 65BSP Inlet X NSW Outlet
PHV -65BSP-SA-SS	R/A 65BSP Inlet X SA Outlet
PHV -65BSP-QRT-SS	R/A 65BSP Inlet X QRT Outlet
PHV -65BSP-BSP-SS	R/A 65BSP Inlet X BSP Outlet
PHV -65BSP-BI-SS	R/A 65BSP Inlet X BI Outlet

HYDRANT RISER ASSEMBLIES - STANDARD TO AS2419.1

SINGLE 100MM

RHSS100	Assy - Hydrant Riser 100mm Single Endrun	RG - Storz
RHSC100	Assy - Hydrant Riser 100mm Single Endrun	RG - CFA
RHS5V100	Assy - Hydrant Riser 100mm Single Endrun	RG - MFB 5v
RHSQ100	Assy - Hydrant Riser 100mm Single Endrun	RG - QRT
RHSN100	Assy - Hydrant Riser 100mm Single Endrun	RG - NSW
Dual 100mm		
RHDS100	Assy - Hydrant Riser 100mm Dual Bullhead	RG - Storz
RHDC100	Assy - Hydrant Riser 100mm Dual Bullhead	RG - CFA
RHD5V100	Assy - Hydrant Riser 100mm Dual Bullhead	RG - MFB 5v
RHDQ100	Assy - Hydrant Riser 100mm Dual Bullhead	RG - QRT
RHDN100	Assy - Hydrant Riser 100mm Dual Bullhead	RG - NSW



DUAL 150MM

RHDS150	Assy - Hydrant Riser 150mm Bullhead Dual	RG - Storz
RHDC150	Assy - Hydrant Riser 150mm Bullhead Dual	RG - CFA
RHD5V150	Assy - Hydrant Riser 150mm Bullhead Dual	RG - MFB 5v
RHDQ150	Assy - Hydrant Riser 150mm Bullhead Dual	RG - QRT
RHDN150	Assy - Hydrant Riser 150mm Bullhead Dual	RG - NSW

QUAD 150MM

RHQS150	Assy - Hydrant Riser 150mm Quad	RG - Storz
RHQC150	Assy - Hydrant Riser 150mm Quad	RG - CFA
RHQ5V150	Assy - Hydrant Riser 150mm Quad	RG - MFB 5v
RHQQ150	Assy - Hydrant Riser 150mm Quad	RG - QRT
RHQN150	Assy - Hydrant Riser 150mm Quad	RG - NSW

Code	Description	Size
HYDRANT RISER ASSEMBLIES - MEDIUM GALVANISED		
SINGLE 100MM ENDRUN RISER		
RHSS100-M	Assy - M/G HYDRANT Riser 100mm Single Endrun	RG - Storz
RHSC100-M	Assy - M/G HYDRANT Riser 100mm Single Endrun	RG - CFA
RHS5V100-M	Assy - M/G HYDRANT Riser 100mm Single Endrun	RG - MFB 5v
RHSQ100-M	Assy - M/G HYDRANT Riser 100mm Single Endrun	RG - QRT
RHSN100-M	Assy - M/G HYDRANT Riser 100mm Single Endrun	RG - NSW
DUAL 100MM BULLHEAD RISER		
RHDS100-M	Assy - M/G HYDRANT Riser 100mm Dual Bullhead	RG - Storz
RHDC100-M	Assy - M/G HYDRANT Riser 100mm Dual Bullhead	RG - CFA
RHD5V100-M	Assy - M/G HYDRANT Riser 100mm Dual Bullhead	RG - MFB 5v
RHDQ100-M	Assy - M/G HYDRANT Riser 100mm Dual Bullhead	RG - QRT
RHDN100-M	Assy - M/G HYDRANT Riser 100mm Dual Bullhead	RG - NSW
DUAL 150MM RISER		
RHDS150-M	Assy - M/G HYDRANT Riser 150mm Dual	RG - Storz
RHDC150-M	Assy - M/G HYDRANT Riser 150mm Dual	RG - CFA
RHD5V150-M	Assy - M/G HYDRANT Riser 150mm Dual	RG - MFB 5v
RHDQ150-M	Assy - M/G HYDRANT Riser 150mm Dual	RG - QRT
RHDN150-M	Assy - M/G HYDRANT Riser 150mm Dual	RG - NSW
QUAD 150MM RISER		
RHQS150-M	Assy - M/G HYDRANT Riser 150mm Quad	RG - Storz
RHQC150-M	Assy - M/G HYDRANT Riser 150mm Quad	RG - CFA
RHQ5V150-M	Assy - M/G HYDRANT Riser 150mm Quad	RG - MFB 5v
RHQQ150-M	Assy - M/G HYDRANT Riser 150mm Quad	RG - QRT
RHQN150-M	Assy - M/G HYDRANT Riser 150mm Quad	RG - NSW
*Special Order		
HYDRANT RISER ASSEMBLIES - STAINLESS STEEL		
SINGLE 100MM ENDRUN RISER		
RHSS100-SS	Assy - S/S HYDRANT Riser 100mm Single Endrun	RG - Storz
RHSC100-SS	Assy - S/S HYDRANT Riser 100mm Single Endrun	RG - CFA
RHS5V100-SS	Assy - S/S HYDRANT Riser 100mm Single Endrun	RG - MFB 5v
RHSQ100-SS	Assy - S/S HYDRANT Riser 100mm Single Endrun	RG - QRT
RHQN100-SS	Assy - S/S HYDRANT Riser 100mm Single Endrun	RG - NSW
DUAL 100MM BULLHEAD RISER		
RHDS100-SS	Assy - S/S HYDRANT Riser 100mm Dual Bullhead	RG - Storz
RHDC100-SS	Assy - S/S HYDRANT Riser 100mm Dual Bullhead	RG - CFA
RHD5V100-SS	Assy - S/S HYDRANT Riser 100mm Dual Bullhead	RG - MFB 5v

Code	Description	Size
RHDQ100-SS	Assy - S/S HYDRANT Riser 100mm Dual Bullhead	RG - QRT
RHDN100-SS	Assy - S/S HYDRANT Riser 100mm Dual Bullhead	RG - NSW

DUAL 150MM RISER

RHDS150-SS	Assy - S/S HYDRANT Riser 150mm Bullhead Dual	RG - Storz
RHDC150-SS	Assy - S/S HYDRANT Riser 150mm Bullhead Dual	RG - CFA
RHD5V150-SS	Assy - S/S HYDRANT Riser 150mm Bullhead Dual	RG - MFB 5v
RHDQ150-SS	Assy - S/S HYDRANT Riser 150mm Bullhead Dual	RG - QRT
RHDN150-SS	Assy - S/S HYDRANT Riser 150mm Bullhead Dual	RG - NSW

QUAD 150MM RISER

RHQS150-SS	Assy - S/S HYDRANT Riser 150mm Quad	RG - Storz
RHQC150-SS	Assy - S/S HYDRANT Riser 150mm Quad	RG - CFA
RHQ5V150-SS	Assy - S/S HYDRANT Riser 150mm Quad	RG - MFB 5v
RHQQ150-SS	Assy - S/S HYDRANT Riser 150mm Quad	RG - QRT
RHQN150-SS	Assy - S/S HYDRANT Riser 150mm Quad	RG - NSW

**Special Order*

**All Hydrant Risers are supplied with an additional coupling and RG Copper Brazing Adaptor*

HYDRANT ACCESSORIES

CAPN&CH-STZ	Nylon Cap & Chain for Storz Coupling.
CAPN&CH-CFA	Nylon Cap & Chain for CFA Coupling.
CAPN&CH-5VT	Nylon Cap & Chain for 5vt Coupling.
CAPN&CH-QRT	Nylon Cap & Chain for QRT Coupling.
CAPN&CH-NSW	Nylon Cap & Chain for NSW Coupling.
CAPN&CH-SA	Nylon Cap & Chain for SA Coupling.
HV-WHEEL	Hydrant Valve Wheel Handle
HVCOVLOCK	Hydrant lockout cap
PADLOCK-003LW	Padlock 003 Lockwood with Key
PADLOCK-003BR	Padlock 003 Brass with Key
HVNEDVC	Ned Kelly Hydrant Valve Cover
ENDRUN100X80	End Run Tee 100mm x 80mm RG (65mm BSP Internal Thread)
ENDRUN100X80X25	End Run Tee 100mm x 80mm x 25mm BSP Hose Reel O/Let
BULLHEAD100	Bullhead Tee 100mm x 80mm x 80mm
BULLHEAD150	Bullhead Tee 150mm x 80mm x 80mm

**For all Hydrant Accessory Enquiries please contact Sales.*



Code **Description** **Size**

BOOSTER HEADS AND BOOSTER RISER ASSEMBLIES

DUAL BOOSTER HEADS

BOTTOM ENTRY - ROLL GROOVED

BODBERGCFASS
BODBERGSTZSS
BODBERG5VSS
BODBERQRTSS
BODBERGNSWSS


100mm CFA
100mm Stortz
100mm 5v MFB
100mm QRT
100mm NSW



REAR / BACK ENTRY - ROLL GROOVED

BODRERGCFASS
BODRERGSTZSS
BODRERG5VSS
BODRERQRTSS
BODRERGNSWSS

100mm CFA
100mm Stortz
100mm 5v MFB
100mm QRT
100mm NSW



QUAD BOOSTERS

Utilise 2 x Back Entry Dual 100mm Boosters

* All Booster Heads are supplied with a 63mm Pressure Gauge, Gauge Cock, Bib Cock assy and Caps or Plugs

BOOSTER RISER ASSEMBLIES STANDARD TO AS2419.1

DUAL BOOSTER

BRDS100	ASSY - Dual Booster B/E and Riser RG 100mm Stortz
BRDC100	ASSY - Dual Booster B/E and Riser RG 100mm CFA
BRD5V100	ASSY - Dual Booster B/E and Riser RG 100mm 5vt
BRDQ100	ASSY - Dual Booster B/E and Riser RG 100mm QRT
BRDN100	ASSY - Dual Booster B/E and Riser RG 100mm NSW

QUAD BOOSTER

BRQS150	ASSY - Quad Booster B/E and Riser RG 150mm Stortz
BRQC150	ASSY - Quad Booster B/E and Riser RG 150mm CFA
BRQ5V150	ASSY - Quad Booster B/E and Riser RG 150mm 5vt
BRQQ150	ASSY - Quad Booster B/E and Riser RG 150mm QRT
BRQN150	ASSY - Quad Booster B/E and Riser RG 150mm NSW

Code **Description** **Size**

BOOSTER RISER ASSEMBLIES - MEDIUM GALVANISED

DUAL BOOSTER M/G

BRDS100-M	ASSY - Dual Booster B/E and Riser RG 100mm Storz	
BRDC100-M	ASSY - Dual Booster B/E and Riser RG 100mm CFA	
BRD5V100-M	ASSY - Dual Booster B/E and Riser RG 100mm 5vt	
BRDQ100-M	ASSY - Dual Booster B/E and Riser RG 100mm QRT	
BRDN100-M	ASSY - Dual Booster B/E and Riser RG 100mm NSW	

QUAD BOOSTER M/G

BRQS150-M	ASSY - Quad Booster B/E and Riser RG 150mm Storz	
BRQC150-M	ASSY - Quad Booster B/E and Riser RG 150mm CFA	
BRQ5V150-M	ASSY - Quad Booster B/E and Riser RG 150mm 5vt	
BRQQ150-M	ASSY - Quad Booster B/E and Riser RG 150mm QRT	
BRQN150-M	ASSY - Quad Booster B/E and Riser RG 150mm NSW	

**Special Order*

BOOSTER RISER ASSEMBLIES - STAINLESS STEEL

DUAL BOOSTER S/S

BRDS100-SS	ASSY - Dual Booster B/E and Riser RG 100mm Storz	
BRDC100-SS	ASSY - Dual Booster B/E and Riser RG 100mm CFA	
BRD5V100-SS	ASSY - Dual Booster B/E and Riser RG 100mm 5vt	
BRDQ100-SS	ASSY - Dual Booster B/E and Riser RG 100mm QRT	
BRDN100-SS	ASSY - Dual Booster B/E and Riser RG 100mm NSW	

QUAD BOOSTER S/S

BRQS150-SS	ASSY - Quad Booster B/E and Riser RG 150mm Storz	
BRQC150-SS	ASSY - Quad Booster B/E and Riser RG 150mm CFA	
BRQ5V150-SS	ASSY - Quad Booster B/E and Riser RG 150mm 5vt	
BRQQ150-SS	ASSY - Quad Booster B/E and Riser RG 150mm QRT	
BRQN150-SS	ASSY - Quad Booster B/E and Riser RG 150mm NSW	

**Special Order*

H-PATTERNS: BOOSTER AND FEED HYDRANT ASSEMBLIES

H-PATTERN (AS2419.1)

BFHDS100	Booster & Feed Hyd RG 100mm Dual - Storz
BFHDC100	Booster & Feed Hyd RG 100mm Dual - CFA
BFHDQ100	Booster & Feed Hyd RG 100mm Dual - QLD
BFHDN100	Booster & Feed Hyd RG 100mm Dual - NSW

BFHDS150	Booster & Feed Hyd 150mm Dual - Storz
BFHDC150	Booster & Feed Hyd 150mm Dual - CFA
BFHDQ151	Booster & Feed Hyd 150mm Dual - QRT
BFHDN152	Booster & Feed Hyd 150mm Dual - NSW

Code	Description	Size
BFHQS150	Booster & Feed Hyd 150mm Quad - Storz	
BFHQC150	Booster & Feed Hyd 150mm Quad - CFA	
BFHQQ150	Booster & Feed Hyd 150mm Quad - QRT	
BFHQN150	Booster & Feed Hyd 150mm Quad - NSW	

H-PATTERNS W SDCV AND BI-PASS TRIMMED TO WATERBOARD REGULATIONS (VIC ONLY)
DUAL 100MM

BFHDS100SEW	Booster & SS Feed Hyd 100mm Dual w SDCV - Storz SEW
BFHDS100CWW	Booster & SS Feed Hyd 100mm Dual w SDCV - Storz CWW
BFHDS100YVW	Booster & SS Feed Hyd 100mm Dual w SDCV - Storz YVW
BFHDC100SEW	Booster & SS Feed Hyd 100mm Dual w SDCV - CFA SEW
BFHDC100CWW	Booster & SS Feed Hyd 100mm Dual w SDCV - CFA CWW
BFHDC100YVW	Booster & SS Feed Hyd 100mm Dual w SDCV - CFA YVW
BFHD5V100CWW	Booster & SS Feed Hyd 100mm Dual w SDCV - 5V CWW

DUAL 150MM

BFHDS150SEW	Booster & SS Feed Hyd 150mm Dual w SDCV - Storz SEW
BFHDS150CWW	Booster & SS Feed Hyd 150mm Dual w SDCV - Storz CWW
BFHDS150YVW	Booster & SS Feed Hyd 150mm Dual w SDCV - Storz YVW
BFHDC150SEW	Booster & SS Feed Hyd 150mm Dual w SDCV - CFA SEW
BFHDC150CWW	Booster & SS Feed Hyd 150mm Dual w SDCV - CFA CWW
BFHDC150YVW	Booster & SS Feed Hyd 150mm Dual w SDCV - CFA YVW
BFHDC5V150CWW	Booster & SS Feed Hyd 150mm Dual w SDCV - 5V CWW

QUAD 150MM

BFHQS150SEW	Booster & SS Feed Hyd 150mm Quad w SDCV - Storz SEW
BFHQS150CWW	Booster & SS Feed Hyd 150mm Quad w SDCV - Storz CWW
BFHQS150YVW	Booster & SS Feed Hyd 150mm Quad w SDCV - Storz YVW
BFHQC150SEW	Booster & SS Feed Hyd 150mm Quad w SDCV - CFA SEW
BFHQC150CWW	Booster & SS Feed Hyd 150mm Quad w SDCV - CFA CWW
BFHQC150YVW	Booster & SS Feed Hyd 150mm Quad w SDCV - CFA YVW
BFHQ5V150CWW	Booster & SS Feed Hyd 150mm Quad w SDCV - 5V CWW

**For Other Water Agency Detector Check Bi-Pass arrangements please contact Sales.*

STANDPIPES, STORTZ SUCTION CONNECTIONS AND BRIGADE ADAPTORS

HYDRANT STANDPIPES

STPCFA	CFA
STP5V	5vt (MFB)
STPSTZ	Stortz
STPQRT	QRT
STPNSW	NSW
STPSA	SA



Code	Description	Size
STORTZ SUCTION CONNECTIONS (ADAPTORS) WITH CAP		
SSA125100075		125 BSP x 100 x 75
SSA100075RG		100 RG x 100 x 75
SSA150100075RG		150 RG x 100 x 75
SSA150100075FL		150 FLG x 100 x 75
SSA150125090		150 BSP x 125 x 90
SSA150125090RG		150 RG x 125 x 90
SSA150125090FL		150 FLG x 125 x 90
SSA1501259075		150 BSP x 125 x 75
SSA1501259075RG		150 RG x 90 x 75
SSA1501259075FL		150 FLG x 125 x 90 x75

Individual adaptors available on request. Please contact sales for pricing enquiries

STORTZ ADAPTORS

Storz Adaptors are used to form the easiest and quickest connection from Hose Couplings to Fire Fighting Fittings such as branch pipes, nozzles, hydrant boosters, pumps etc.

- Specifications: Aluminium Alloy- Forged Pressure Rating: 1600Kpa

STORTZ FEMALE ADAPTORS

AD-SZ-25-1NH-F	Storz 25 x 1" NH FEMALE
AD-SZ-25-12BSP-F	Storz 25 x 12 BSP Female
AD-SZ-25-19BSP-F	Storz 25 x 19 BSP Female
AD-SZ-25-25BSP-F	Storz 25 x 25 BSP Female
AD-SZ-38-38BSP-F	Storz 38 x 38 BSP Female
AD-SZ-52-38BSP-F	Storz 52 x 38 BSP Female
AD-SZ-52-52BSP-F	Storz 52 x 52 BSP Female
AD-SZ-65-38BSP-F	Storz 65 x 38 BSP Female
AD-SZ-65-52BSP-F	Storz 65 x 52 BSP Female
AD-SZ-65-65BSP-F	Storz 65 x 65 BSP Female
AD-SZ-65-2.5NH-F	Storz 65 x 2.5" NH Female
AD-SZ-65-CFA-F	Storz 65 x CFA Female
AD-SZ-65-MFB-F	Storz 65 x MFB Female
AD-SZ-65-NSW-F	Storz 65 x NSW Female
AD-SZ-65-QRT-F	Storz 65 x QRT Female
AD-SZ-65-SA-F	Storz 65 x SA Female
AD-SZ-65-BI-F	Storz 65 x BI Female
AD-SZ-75-52BSP-F	Storz 75 x 52 BSP Female
AD-SZ-75-65BSP-F	Storz 75 x 65 BSP Female
AD-SZ-75-75BSP-F	Storz 75 x 75 BSP Female
AD-SZ-90-65BSP-F	Storz 90 x 65 BSP Female
AD-SZ-90-75BSP-F	Storz 90 x 75 BSP Female
AD-SZ-100-65BSP-F	Storz 100 x 65 BSP Female
AD-SZ-100-75BSP-F	Storz 100 x 75 BSP Female
AD-SZ-100-100BSP-F	Storz 100 x 100 BSP Female
AD-SZ-100-CFA-F	Storz 100x CFA Female
AD-SZ-125-65BSP-F	Storz 125 x 65BSP Female
AD-SZ-125-100BSP-F	Storz 125 x 100 BSP Female
AD-SZ-125-125BSP-F	Storz 125 x 125 BSP Female



Code	Description	Size
AD-SZ-125-4.5NH-F	Storz 125 x 4.5" NH Female	
AD-SZ-125-5NH-F	Storz 125 x 5" NH Female	
AD-SZ-150-150BSP-F	Storz150 x 150 BSP Female	

STORTZ ADAPTORS - MALE TO FEMALE

AD-SZ-25-1NH-M	Storz 25 x 1" NH Male
AD-SZ-25-1NPSH-M	Storz 25 x 1" NPSH Male
AD-SZ-25-12BSP-M	Storz 25 x 12 BSP Male
AD-SZ-25-19BSP-M	Storz 25 x 19 BSP Male
AD-SZ-25-25BSP-M	Storz 25 x 25 BSP Male
AD-SZ-38-25BSP-M	Storz 38x 25 BSP Male
AD-SZ-38-38BSP-M	Storz 38 x 38 BSP Male
AD-SZ-52-38BSP-M	Storz 52 x 38 BSP Male
AD-SZ-52-52BSP-M	Storz 52x 52 BSP Male
AD-SZ-65-38BSP-M	Storz 65 x 38 BSP Male
AD-SZ-65-52BSP-M	Storz 65 x 52 BSP Male
AD-SZ-65-65BSP-M	Storz 55 x 65 BSP Male
AD-SZ-65-2.5NH-M	Storz 65 x 2.5" NH Male
AD-SZ-65-CFA-M	Storz 65 x CFA Male
AD-SZ-65-MFB-M	Storz 65 x MFB Male
AD-SZ-65-NSW-M	Storz 65 x NSW Male
AD-SZ-65-QRT-M	Storz 65 x QRT Male
AD-SZ-65-SA-M	Storz 65 x SA Male
AD-SZ-65-BI-M	Storz 65 x BI Male
AD-SZ-75-52BSP-M	Storz 75 x 52 BSP Male
AD-SZ-75-65BSP-M	Storz 75 x 65 BSP Male
AD-SZ-75-75BSP-M	Storz 75 x75 BSP Male
AD-SZ-90-65BSP-M	Storz 90 x 65 BSP Male
AD-SZ-90-75BSP-M	Storz 90 x 75 BSP Male
AD-SZ-100-100BSP-M	Storz100 x 100 BSP Male
AD-SZ-125-100BSP-M	Storz125 x 100 BSP Male
AD-SZ-125-125BSP-M	Storz 125 x 125 BSP Male
AD-SZ-150-150BSP-M	Storz 150 x 150 BSP Male



STORTZ X STORTZ REDUCERS

Storz to Storz Reducers are used to connect the Hoses or Fittings having different sizes. The Storz Reducers are available with Clamp Fittings on both ends, thereby enabling to connect the required reduced sizes. The seals are provided on both sides of the Storz formation.

AD-SZR-38-25	Storz 38 x Storz 25
AD-SZR-52-25	Storz 52 x Storz 25
AD-SZR-52-38	Storz 52 x Storz 38
AD-SZR-65-25	Storz 65 x Storz25
AD-SZR-65-38	Storz 65 x Storz 38
AD-SZR-65-52	Storz 65x Storz 52
AD-SZR-75-52	Storz 75 x Storz 52
AD-SZR-75-65	Storz 75 x Storz 65
AD-SZR-90-65	Storz 90 x Storz 65
AD-SZR-90-75	Storz 90x Storz 75



Code	Description	Size
AD-SZR-100-75	Storz 100 x Storz 75	
AD-SZR-100-90	Storz 100 x Storz 90	
AD-SZR-150-100	Storz 150 x Storz 100	
AD-SZR-150-125	Storz 150 x Storz 125	
STORTZ CAPS WITH CHAIN		
AD-SZC-25	Storz 25 CAP	25mm
AD-SZC-38	Storz 38 CAP	38mm
AD-SZC-52	Storz 52 CAP	52mm
AD-SZC-65	Storz 65 CAP	65mm
AD-SZC-75	Storz 75 CAP	75mm
AD-SZC-90	Storz 90 CAP	90mm
AD-SZC-100	Storz 100 CAP	100mm
AD-SZC-125	Storz 125 CAP	125mm
AD-SZC-150	Storz 150 CAP	150mm

BRIGADE ADAPTORS - CFA, MFB, QRT AND SA

- Specifications: Brass and Aluminium Alloy - all adaptors are Forged.
- Pressure Rating: 1600Kpa

BRIGADE ADAPTORS BRASS - MALE TO FEMALE (CFA, MFB, QRT, SA)

AD-CFA-65M-38BSPF-B	65CFA Male x 38 BSP Female
AD-CFA-65M-50BSPF-B	65CFA Male x 50 BSP Female
AD-CFA-65M-65BSPF-B	65CFA Male x 65 BSP Female
AD-CFA-65M-65MFBF-B	65CFA Male x 65 MFB Female
AD-MFB-65M-38BSPF-B	65MFB Male x 38 BSP Female
AD-MFB-65M-50BSPF-B	65MFB Male x 50 BSP Female
AD-MFB-65M-65BSPF-B	65MFB Male x 65 BSP Female
AD-QRT-65M-38BSPF-B	65QRT Male x 38 BSP Female
AD-QRT-65M-50BSPF-B	65QRT Male x 50 BSP Female
AD-QRT-65M-65BSPF-B	65QRT Male x 65 BSP Female
AD-SA-65M-38BSPF-B	65SA Male x 38 BSP Female
AD-SA-65M-50BSPF-B	65SA Male x 50 BSP Female
AD-SA-65M-65BSPF-B	65SA Male x 65 BSP Female



Code	Description	Size
BRIGADE ADAPTORS BRASS - MALE TO MALE (CFA, MFB, QRT, SA)		
AD-CFA-65M-38BSPM-B	65CFA Male x 38 BSP Male	
AD-CFA-65M-50BSPM-B	65CFA Male x 50 BSP Male	
AD-CFA-65M-65BSPM-B	65CFA Male x 65 BSP Male	
AD-MFB-65M-38BSPM-B	65MFB Male x 38 BSP Male	
AD-MFB-65M-50BSPM-B	65MFB Male x 50 BSP Male	
AD-MFB-65M-65BSPM-B	65MFB Male x 65 BSP Male	
AD-QRT-65M-38BSPM-B	65QRT Male x 38 BSP Male	
AD-QRT-65M-50BSPM-B	65QRT Male x 50 BSP Male	
AD-QRT-65M-65BSPM-B	65QRT Male x 65 BSP Male	
AD-SA-65M-38BSPM-B	65SA Male x 38 BSP Male	
AD-SA-65M-50BSPM-B	65SA Male x 50 BSP Male	
AD-SA-65M-65BSPM-B	65SA Male x 65 BSP Male	



BRIGADE ADAPTORS BRASS - FEMALE TO MALE (CFA, MFB, QRT, SA)

AD-CFA-65F-19BSPM-B	65CFA Female X 19 BSP Male
AD-CFA-65F-25BSPM-B	65CFA Female X 25BSP Male
AD-CFA-65F-32BSPM-B	65CFA Female X 32BSP Male
AD-CFA-65F-38BSPM-B	65CFA Female X 38 BSP Male
AD-CFA-65F-50BSPM-B	65CFA Female X 50BSP Male
AD-CFA-65F-65BSPM-B	65CFA Female X 65 BSP Male
AD-CFA-65F-65MFBM-B	65CFA Female X 65 MFB Male
AD-MFB-65F-19BSPM-B	65MFB Female X 19BSP Male
AD-MFB-65F-25BSPF-B	65MFB Female X 25BSP Female
AD-MFB-65F-32BSPF-B	65MFB Female X 32BSP Female
AD-MFB-65F-38BSPF-B	65MFB Female X 38BSP Female
AD-MFB-65F-50BSPF-B	65MFB Female X 50BSP Female
AD-MFB-65F-65BSPF-B	65MFB Female X 65BSP Female
AD-QRT-65F-19BSPF-B	65QRT Female X 19 BSP Female
AD-QRT-65F-25BSPF-B	65QRT Female X 25 BSP Female
AD-QRT-65F-32BSPF-B	65QRT Female X 32 BSP Female
AD-QRT-65F-38BSPF-B	65QRT Female X 38BSP Female
AD-QRT-65F-50BSPF-B	65QRT Female X 50BSP Female
AD-QRT-65F-65BSPF-B	65QRT Female X 65 BSP Female
AD-SA-65F-19BSPF-B	65SA Female X 19 BSP Female
AD-SA-65F-25BSPF-B	65SA Female X 25 BSP Female
AD-SA-65F-32BSPF-B	65SA Female X 32 BSP Female
AD-SA-65F-38BSPF-B	65SA Female X 38 BSP Female
AD-SA-65F-50BSPF-B	65SA Female X 50 BSP Female
AD-SA-65F-65BSPF-B	65SA Female X 65 BSP Female



Code	Description	Size
BRIGADE ADAPTORS BRASS - SWIVEL ADAPTORS (CFA, SA)		

PSW-65CFAf-65BSPF-B	Swivel 65CFA Female X 65 BSP Female	
PSW-65CFAf-65CFAf-B	Swivel 65CFA Female X 65 CFA Female	
PSW-65CFAf-80BSPF-B	Swivel 65CFA Female X 80 BSP Female	
PSW-65CFAf-65BSPM-B	Swivel 65CFA Female X 65 BSP Male	
PSW-65CFAf-80BSPM-B	Swivel 65CFA Female X 80 BSP Male	
PSW-65SAf-65BSPM-B	Swivel 65SA Female X 65 BSP Male	



BRIGADE ADAPTORS ALUMINIUM - FEMALE TO MALE (QRT, SA)

AD-QRT-65F-38BSPM-A	65QRT Female X 38 BSP Male
AD-QRT-65F-50BSPM-A	65QRT Female X 50 BSP Male
AD-QRT-65F-65BSPM-A	65QRT Female X 65 BSP Male

AD-SA-65F-38BSPF-A	65SA Female X 38 BSP Male
AD-SA-65F-50BSPF-A	65SA Female X 50 BSP Male
AD-SA-65F-65BSPF-A	65SA Female X 65 BSP Male



BRIGADE ADAPTORS ALUMINIUM - MALE TO FEMALE (QRT, SA)

AD-QRT-65M-38BSPF-A	65QRT Male X 38 BSP Female
AD-QRT-65M-50BSPF-A	65QRT Male X 50 BSP Female
AD-QRT-65M-65BSPF-A	65QRT Male X 65 BSP Female

AD-SA-65M-38BSPF-A	65SA Male X 38 BSP Female
AD-SA-65M-50BSPF-A	65SA Male X 50 BSP Female
AD-SA-65M-65BSPF-A	65SA Male X 65 BSP Female



BRIGADE ADAPTORS ALUMINIUM - SWIVEL (QRT, SA)

AD-SW-65QF-38BSPM-A	Swivel 65QRT Female x 38 BSP Male
AD-SW-65QF-50BSPM-A	Swivel 65QRT Female x 50 BSP Male
AD-SW-65QF-65BSPM-A	Swivel 65QRT Female x 65 BSP Male

AD-SW-65QF-38BSPF-A	Swivel 65QRT Female x 38 BSP female
AD-SW-65QF-50BSPF-A	Swivel 65QRT Female x 50 BSP female
AD-SW-65QF-65BSPF-A	Swivel 65QRT Female x 65 BSP female

AD-SW-65SF-38BSPM-A	Swivel 65SA Female x 38 BSP male
AD-SW-65SF-50BSPM-A	Swivel 65SA Female x 50 BSP male
AD-SW-65SF-65BSPM-A	Swivel 65SA Female x 65 BSP male



NIPPLES - ALUMINIUM MALE

HNIP-1	3" BSP x 2.5" BSP Nipple
HNIP-2	4" BSP x 2.5" BSP Nipple
HNIP-3	4" BSP x 3" BSP Nipple
HNIP-4	5" BSP x 2.5" BSP Nipple
HNIP-5	5" BSP x 3" BSP Nipple

Code	Description	Size
HNIP-6	5" BSP x 4" BSP Nipple	
HNIP-7	6" BSP x 5" BSP Nipple	
HNIP-8	5" RND x 4" BSP Nipple	
HNIP-9	5" RND x 5" BSP Nipple	
HNIP-10	6" RND x 6" BSP Nipple	
HNIP-11	6" RND x 6" BSP Nipple	

COUPLINGS - STORTZ

Storz Couplings have the Forged Clamping Nut. The major benefit of using Storz couplings is that the clamp fitting is free to rotate on the tail, which stops the hose from twisting and from rotating against the seal.

- Aluminium Forged Alloy
- Pressure Rating: 1600Kpa

SCZ-25-12T	Storz 25 x 12 Tail Coupling
SCZ-25-19T	Storz 25 x 19 Tail Coupling
SCZ-25-25T	Storz 25 x 25 Tail Coupling
SCZ-38-19T	Storz 38 x 19 Tail Coupling
SCZ-38-25T	Storz 38 x 25 Tail Coupling
SCZ-38-32T	Storz 38 x 32 Tail Coupling
SCZ-38-38T	Storz 38 x 38 Tail Coupling
SCZ-52-25T	Storz 52 x 25 Tail Coupling
SCZ-52-38T	Storz 52 x 38 Tail Coupling
SCZ-52-52T	Storz 52 x 52 Tail Coupling
SCZ-65-38T	Storz 65 x 38 Tail Coupling
SCZ-65-52T	Storz 65 x 52 Tail Coupling
SCZ-65-65T	Storz 65 x 65 Tail Coupling
SCZ-65-70T	Storz 65 x 70 Tail Coupling
SCZ-75-65T	Storz 75 x 65 Tail Coupling
SCZ-75-70T	Storz 75 x 70 Tail Coupling
SCZ-75-75T	Storz 75 x 75 Tail Coupling
SCZ-90-90T	Storz 90 x 90 Tail Coupling
SCZ-100-100T	Storz 100 x 100 Tail Coupling
SCZ-125-125T	Storz 125 x 125 Tail Coupling
SCZ-150-150T	Storz 150 x 150 Tail Coupling



MALE COUPLING TAIL - BRASS

H-25BSPM-25T-B	25BSP Male x 25 Grooved Tail
H-38BSPM-38T-B	38BSP Male x 38 Grooved Tail
H-50BSPM-50T-B	50BSP Male x 50 Grooved Tail
H-65CFAM-32T-B	65CFA Male x 32 Grooved Tail
H-65CFAM-38T-B	65CFA Male x 38 Grooved Tail
H-65CFAM-50T-B	65CFA Male x 50 Grooved Tail
H-65CFAM-65T-B	65CFA Male x 65 Grooved Tail
H-65CFAM-89T-B	65CFA Male x 89 Grooved Tail
H-65MFBM-38T-B	65MFB Male x 38 Grooved Tail
H-65MFBM-50T-B	65MFB Male x 50 Grooved Tail
H-65MFBM-65T-B	65MFB Male x 65 Grooved Tail

Code	Description	Size
H-65NSWM-38T-B	65NSW Male x 38 Grooved Tail	
H-65NSWM-50T-B	65NSW Male x 50 Grooved Tail	
H-65NSWM-65T-B	65NSW Male x 65 Grooved Tail	
H-65QRTM-38T-B	65QRT Male x 38 Grooved Tail	
H-65QRTM-65T-B	65QRT Male x 65 Grooved Tail	

FEMALE COUPLING TAIL - BRASS

H-25BSPF-25T-B	25BSP Female x 25 Grooved Tail
H-38BSPF-38T-B	38BSP Female x 38 Grooved Tail
H-65CFAF-32T-B	65CFA Female x 32 Grooved Tail
H-65CFAF-38T-B	65CFA Female x 38 Grooved Tail
H-65CFAF-50T-B	65CFA Female x 50 Grooved Tail
H-65CFAF-65T-B	65CFA Female x 65 Grooved Tail
H-65CFAF-89T-B	65CFA Female x 89 Grooved Tail
H-65MFBF-38T-B	65MFB Female x 38 Grooved Tail
H-65MFBF-50T-B	65MFB Female x 50 Grooved Tail
H-65MFBF-65T-B	65MFB Female x 65 Grooved Tail
H-65NSWF-38T-B	65NSW Female x 38 Grooved Tail
H-65NSWF-50T-B	65NSW Female x 50 Grooved Tail
H-65NSWF-65T-B	65NSW Female x 65 Grooved Tail
H-65QRTF-38T-B	65QRT Female x 38 Grooved Tail
H-65QRTF-65T-B	65QRT Female x 65 Grooved Tail

MALE COUPLING - STAINLESS STEEL

H-65CFAM-38T-S	65CFA Male x 38 Grooved Tail
H-65CFAM-65T-S	65CFA Male x 65 Grooved Tail

FEMALE COUPLING - STAINLESS STEEL

H-65CFAF-38T-S	65CFA Female x 38 Grooved Tail
H-65CFAF-65T-S	65CFA Female x 65 Grooved Tail

MALE COUPLING - ALUMINIUM

H-65QRTM-38T-A	65QRT Male x 38 Grooved Tail
H-65SAM-38T-A	65SA Male x 38 Grooved Tail
H-65QRTM-65T-A	65QRT Male x 65 Grooved Tail
H-65SAM-65T-A	65SA Male x 65 Grooved Tail

FEMALE COUPLING - ALUMINIUM

H-65QRTF-38T-A	65QRT Female x 38 Grooved Tail
H-65SAF-38T-A	65SA Female x 38 Grooved Tail
H-65QRTF-65T-A	65QRT Female x 65 Grooved Tail
H-65SAF-65T-A	65SA Female x 65 Grooved Tail

Code	Description	Size
MALE COUPLING - PLASTIC		
H-65CFAM-38T-P	65CFA Male x 38 Grooved Tail	65mm
H-65MFBM-38T-P	65MFB Male x 38 Grooved Tail	65mm
H-65CFAM-65T-P	65CFA Male x 65Grooved Tail	65mm
H-65MFBM-65T-P	65MFB Male x 65 Grooved Tail	65mm
H-65CFAF-38T-P	65CFA Female x 38 Grooved Tail	65mm
H-65MFBF-38T-P	65MFB Female x 38 Grooved Tail	65mm
H-65CFAF-65T-p	65CFA Female x 65Grooved Tail	65mm
H-65MFBF-65T-P	65MFB Female x 65 Grooved Tail	65mm

For all other Stortz and Brigade Fittings and Adaptors please contact Sales

FIRE FIGHTING HOSES (LAY FLAT)

EXCALIBUR

EXCALIBUR is a popular choice for domestic and commercial fire fighting purposes. It is lightweight very easy to handle and quick to deploy.

EXCALIBUR can be supplied as a ready to go Fire Hose Kit. complete with a shut off nozzle and fitted couplings.

Due to Excalibur's synthetic construction it is mildew resistant and therefore maintenance free. It can be compactly stored when not in use.

Excalibur comes with the 12 months full replacement warranty.

EXCALIBUR Hose is manufactured in Australia to AS2792-1992 Standard.

- Can be stored wet
- High burst pressure 3500kPa
- Working pressure 1500kPa
- Mildew resistant for long life
- Many fittings available
- Low friction loss
- Versatile
- Class M



Code **Description** **Size**

CAVALIER

In environments where chemical or toxic spills may complicate fire fighting efforts, CAVALIER Hose has a protective polyurethane cover on the jacket. It is a popular choice for industrial and fire fighting purposes. Apart from being an outstanding fire hose, the CAVALIER is a versatile hose that is also suitable for many high and low pressure liquid transfer jobs. CAVALIER is a sturdy and hardwearing layflat hose that can be easily stored when not in use. The protective polyurethane jacket can be manufactured in a variety of colours, ideal for identification purposes.

- Reliability
- High burst pressure 5250kPa
- Working pressure 2100kPa
- Mildew resistant
- Many fittings available
- Light and quick to deploy
- Easy storage
- Can be stored wet
- Class H
- Australian Standard AS2792



CENTURION

Professional fire brigades need the highest performing layflat fire hose. CENTURION has been approved for use by the NSW Fire Brigade and the CFA, as well as the ADF(Australian Defence Force). For extreme fire fighting conditions, a high pressure (Class H) fire hose is absolutely essential. With CENTURION hose fighting on your side, you have total peace of mind.

The CENTURION layflat fire hose has been constructed with the demands of professional fire fighting units in mind. The internal tightly woven polyester jacket makes this hose suitable for high pressure pumping applications, combined with protection against abrasion and exposure to the elements.

Usually this hose is supplied in 30m lengths but longer lengths can be made up to 200m. This twill-woven fire hose is made from polyester with a synthetic rubber lining and requires no drying after use.

CENTURION hose is manufactured in Australia to AS2792-1992 and carries an approval of the Australian Army DEF 5195A 1992 standard.

- Reliability
- High burst pressure 5250kPa
- Working pressure 2100kPa
- Mildew resistant
- Many fittings available
- Light and quick to deploy
- Easy storage
- Can be stored wet
- Class H
- Australian Standard AS2792



Code **Description** **Size**

SABRE

SABRE is Crusader Hose's premium percolating fire hose. This is a layflat percolating fire hose which allows precision engineered seepage of water under pressure through the hose fabric jacket. This percolating feature forms a water barrier on the hose jacket which protects the hose against the effects of heat and glowing embers.

Sabre fire hose can be manufactured from 25mm to 102mm diameter. Its lightweight yet sturdy construction enables fire fighters to take this hose into dense bushfires, transporting the hose in backpacks. The hose is fully synthetic thus making it mildew resistant. As a result this hose is maintenance free so no drying is required after use.

Depending on the types of fires, you can choose from 3 grades of percolation - low, medium and high.

The SABRE Hose has the Australian Standard AS2792-1992.

- Mildew resistant
- Maintenance free
- Ready for mounting
- Can be stored wet
- Versatile
- Other fittings available
- Working pressure 1500kPa
- Class M



RAPIER

RAPIER is a popular choice for both fire brigades and industrial plant fire protection.

It is a high pressure Type 3 fire hose, which is manufactured with an extruded synthetic rubber cover. This extruded cover protects the hose against abrasion and chemical damage.

The interior lining and exterior coating on the fire hose jacket is made from PVC nitrile. This extruded cover is highly chemical and abrasion resistant. In addition to the practical protection afforded by the polymer cover, the layflat hose is protected from being stained by oils and dirt.

The RAPIER hose has the Australian Defence Force DEF 5195A Standard of approval.

- Reliability
- High burst pressure 5250kPa
- Working pressure 2100kPa
- Mildew resistant for long life
- Other fittings available
- Light and quick to deploy
- Class H
- Australian Standard AS2792



Code Description Size

Hose Type	Excalibur	Cavalier	Centurion	Sabre	Rapier
Burst Pressure	Low Medium	Medium High	High	Medium High	Medium High
Diameter	25mm - 102mm	25mm - 102mm	25mm - 102mm	25mm - 102mm	25mm - 102mm
Cover material	Polyester	PU Coating	Polyester	Percolating	PVC
Colour	White	Red/Any	White	White	Red/Any